

Discover the portable power of Lithium-Ion





GO GO[®]
ENDURANCE **Li**

With the Go Go Endurance Li, traveling has never been easier! This 4-wheel scooter has everything you need for a safe and convenient trip. With the standard 8 AH airline-compliant* lithium-ion battery pack, the Go Go Endurance is perfect for air travel. Feather-touch disassembly provides the portability you need. When you arrive at your destination, enjoy a smooth, comfortable ride with Comfort-Trac Suspension.

PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]



Specifications

Weight capacity	147 kg
Maximum speed ¹	Up to 6,7 km/h
Ground clearance ²	83 mm
Turning radius ²	1225 mm
Length ²	1070 mm
Width ²	521 - 690 mm
Tires	8" solid (front and rear)
Drive	Rear-wheel drive, single motor, 24-volt DC motor
Dual braking system	Regenerative and electromechanical
Total weight without batteries ^{2,4}	41 kg
Battery ²	Type: Lithium Capacity: 8 Ah or 16 Ah
Battery weight ³	8 Ah: 2,5 kg each 16 Ah: 5,5 kg each
Battery charger	Off-board, 3.5 amp (lithium ion)
Range per charge	8 Ah battery: Up to 8 km at 147,5 kg Up to 10,6 km at 91 kg 16 Ah battery: Up to 16 km at 147,5 kg Up to 21.3 km at 91 kg
Standard seating	Type: Molded Plastic Weight: 8,5 kg Material: Black Vinyl Width: 432 mm Depth: 432 mm
Colors	  Garnet Red Euro Grey

Features

- Per charge range up to 21,3 km with 16 Ah⁵ batteries
- Delta tiller with ergonomic wraparound handles lets you operate the scooter with one hand and rest your wrists
- Convenient dual charging ports can charge battery pack on-board or off-board
- Includes two sets of easily changeable, colored panels
- Standard 8 Ah airline-compliant lithium-ion battery pack* or upgrade to 16 Ah MAXX battery pack ⁵.



* Transport of this item on commercial aircraft is subject to regulations and airline policy. Please consult your airline prior to your flight to ensure your Go Go Endurance scooter and its lithium-ion battery are permitted.

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.
5. Does not meet airline requirements.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.